

Private Label Ballasts



NANOLOX
Technology Inc



Nanolux is proud to introduce the opportunity to supply retail stores with their own private labeled ballasts. In the competitive market of digital ballasts, stores may find the need to have their own house brand at a very competitive price. Nanolux has become the leading ballast brand being sold in more countries worldwide than any other brand. The same quality that goes into every Nanolux ballast goes into every private label ballast we manufacture. You will notice that some of the designs are similar to recognizable branded ballasts in the market. That is because Nanolux Technologies provides OEM manufacturing for some of the largest names in the business. The minimum order for private label ballasts is 300 units of any model. All private label ballasts come with a two-year warranty. Full color packaging is also available. Contact your local Nanolux rep for more information



Shipping

All orders will be shipped FOB Salt Lake City, UT. Customers will be responsible for the freight charge from Salt Lake City to their store location. The Nanolux outbound freight discount will be applied to the shipping charge for the best rate.

Order Processing

Packaging Artwork Confirmation.....	7 days
First Order Processing.....	30 days
Ocean Transit.....	21 days

Financial Terms

30% deposit with order

70% balance due at time of shipment from Salt Lake City facility.

Warranty

Nanolux warrants that the mechanical and electronic components of the ballasts to be free of defects in material and workmanship if used under normal operating conditions for a period of two (2) years from the original date of purchase. Defective warrantied product has to be returned to Nanolux and replacement ballasts will be provided on the next processed order. Any products which show signs of misuse or damage will not be warrantied.

PUF FAN SERIES



Input Voltage: 120/240Vac
Input Frequency: 50/60HZ
Power Factor: ≥0.99

THD: <10%
Operating Temperature: -30°C~50°C / -22°F~122°F
Dimming: 50% / 75% / 100%
Ballast size:

(1000W) 278x128x70mm / 10.95x5.04x2.8inch
(600W) 228x128x70mm / 8.96x5.04x2.8inch
(400W) 198.2x107x61mm / 7.81x5.04x2.8inch

Ballast weight:
(1000W) 1.89kg / 5.64 lbs
(600W) 1.5kg / 4.45 lbs
(400W) 1.2kg / 4.01 lbs

Box size:
(1000W) 310x185x71mm / 12.2x7.3x2.80inch
(600W) 265x185x71mm / 10.4x7.3x2.80inch
(400W) 230x170x62mm / 9.1x6.7x2.44inch

PCS/Carton: 8pcs(1000W)/8pcs(600W)/12pcs(400W)
CTNS/Pallet: 30(1000W)/36(600W)/48(400W)ctns

1000W / 600W / 400W
120V / 240V



BUN SERIES



1000W / 600W
120V / 240V

Input Voltage: 120/240Vac
Input Frequency: 50/60HZ
Power Factor: ≥0.99
THD: <10%
Operating Temperature: -30°C~50°C / -22°F~122°F
Dimming: 50% / 75% / 100%
Ballast Size: 365x179x107mm / 14.4x7x4.2inch
Ballast Weight: 5.9kg / 13 lbs
Box Size: 400x220x110mm / 15.7x8.7x4.3inch
PCS/Carton: 4pcs
CTNS/Pallet: 20ctns

BEN SERIES



1000W / 600W
240V

Input Voltage: 240Vac
Input Frequency: 50/60HZ
Power Factor: ≥0.99
THD: <10%
Operating Temperature: -30°C~50°C / -22°F~122°F
Dimming: 50% / 75% / 100%
Ballast Size: (1000W) 356x154x88mm / 14x6.1x3.5inch
Ballast Weight: (1000W) 4.35kg / 9.6 lbs
Box Size: (1000W) 370x190x92mm / 14.6x7.48x3.6inch
PCS/Carton: 4pcs
CTNS/Pallet: 20ctns

OUF FAN SERIES

1000W / 600W / 400W
120V / 240V



Input Voltage: 120/240Vac
Input Frequency: 50/60HZ
Power Factor: ≥0.99
THD: <10%
Operating Temperature: -30°C~50°C / -22°F~122°F
Dimming: 50% / 75% / 100%

Ballast size:

(1000W) 395x84x46.5mm / 13.2x3.3x1.83inch
(600W) 290x84x46.5mm / 11.4x3.3x1.83inch
(400W) 290x84x46.5mm / 11.4x3.3x1.83inch

Ballast weight:

(1000W) 1.1kg / 2.43 lbs
(600W) 0.75kg / 1.65 lbs
(400W) 0.67kg / 1.48 lbs

Box size:

(1000W) 355x150x70mm / 13.9x5.9x2.76inch
(600W) 355x150x70mm / 13.9x5.9x2.76inch
(400W) 355x150x70mm / 13.9x5.9x2.76inch

PCS/Carton: 12pcs(1000W/600W/400W)

CTNS/Pallet: 36ctns(1000W/600W/400W)

1000W / 600W / 400W
120V / 240V

AUF SERIES



Input Voltage: 120/240Vac
Input Frequency: 50/60HZ
Power Factor: ≥0.99
THD: <10%
Operating Temperature: -30°C~50°C / -22°F~122°F
Dimming: 50% / 75% / 100%

Ballast size:

(1000W) 391x112x72mm / 15.4x4.4x2.83inch
(600W) 316x112x72mm / 12.4x4.4x2.83inch
(400W) 277x112x72mm / 10.9x4.4x2.83inch

Ballast weight:

(1000W) 3.16kg / 7.0 lbs
(600W) 2.38kg / 5.25 lbs
(400W) 1.95kg / 4.3 lbs

Box size:

(1000W) 470x183x82mm / 18.5x7.2x3.3inch
(600W) 380x183x82mm / 15.9x7.2x3.3inch
(400W) 334x183x82mm / 13.2x7.2x3.3inch

PCS/Carton: 6pcs

CTNS/Pallet: 36(1000W)/36(600W)/36(400W)ctns



A Digital Revolution

NANOLOX
Technology Inc

For information contact your local
Nanolux Sales Representative.



1180 Holm Road Suite C
Petaluma, CA 94954 USA
Phone: 844-NANOLUX (626-6589)
www.nanoluxtech.com
Email: OEM@Nanoluxtech.com