


# LEDtb F760 Fixture

- ✓ Light weight & compact design
- ✓ Two spectra are available
- ✓ Wide input voltage 100V-277V
- ✓ Efficiency up to 2.9  $\mu\text{mol}/\text{J}$
- ✓ NCCS-RTU&0-10V control



## Features

- **Light weight and compact design**

The size of the whole machine is similar to that of traditional HID lamps, which can perfectly realize 1:1 space replacement. But the efficiency of LED 760W is equivalent to that of traditional HID 1000W.

- **Two light spectrums available for options**

Full spectrum & Red is a good choice throughout full cycle of plant growth, seedling, vegetation and flowering in indoor facilities. Full spectrum & Blue is an ideal formula used in veg and flowering stage in outdoor greenhouses. Special spectrum can be customized as per specific needs.

- **NCCS-RTU&0-10V dimming as simulated sunlight function.**

Control module in the fixture can make the group lighting control ON/OFF available along with 20%~100% precise dimming adjustment.


- **Wide voltage range input**

Applicable for voltage from 120V-277V with excellent adaptability in different power supply conditions.

## Specifications

Product Model	NB-LEDtb F760 Fixture
Product code	80.01.0331
Input power	760W
Dimming	0-10V
Input voltage	AC 120V-277V
Input current	8.5A/7.6-2.7A
Light output PPF	2210 $\mu\text{mol/s}$
Efficiency	2.9 $\mu\text{mol/J}$
Input frequency	50/60Hz
Light distribution	120°
Mounting height	>30" (80cm) above canopy
Operating temperature	0°C~35°C
Operating humidity	0~95%
Thermal management	Passive
Power factor	> 0.97
Total harmonic distortion	< 15%
Requirement of installment	Comply with ETL/CE/EAC certificate
Lifetime L90	> 50,000hrs
IP rating	IP65
Product dimensions	700x246x115mm
Product weight	13.5KG
Packaging method	Carton Box/1PCS
Packing dimensions	745x330x150mm/Carton
Gross weight	14.5KG/Carton
Loading Quantity	20GP: 640 Carton    40GP: 1410 Carton    40HQ: 1650 Carton
Warranty	5 years standard warranty
Region applied	USA, Canada, Australia, EU, etc.
Industry application	Greenhouse, indoor grow room, tent

## Spectrum



Shenzhen Number Energy Saving Corporation

E-mail: sales@sznumber.com Tel: +86-755-28245686 Fax: +86-755-28245689 www.sznumber.com www.nanoluxtech.com  
 No.6, Caiyun 1st Road., Longgang District, Shenzhen, 518172, Guangdong, P.R.China